

## DOSO BOX

DOSO BOX is a machine, used to unravel the fibres and transport them, through a pneumatic and vibrating mechanism, inside the concrete mixer.

Using DOSO BOX the load of fibres is better and safe for the personnel in charge, and the quality of the product is better.

The upload of fibres is done emptying the boxes or the sack inside the hopper of the DOSO BOX. The fibres are unravelled by a vibrating plate and a uniform flow of them is sent inside the pneumatic transporter.

Before to load the fibres it is necessary to put the metallic tube inside the concrete mixer.

DOSO BOX takes the place of two fibres pallets so to improve load and fibres delivery.

It is easily transportable on truck or container, thanks to its dimensions and compactness.

The unravelling machine can be lifted from each side through a lift truck. It can also be moved from above through special hooks for a crane.



Figure 1



Figure 2



Figure 3

### TECHNICAL DETAILS

#### PERFORMANCES:

Maximum hourly production	50/80 kg/min
Allowed box capacity	15/25 kg

#### DETAILS

Power	380 V
Frequency	50 Hz
Power installed	10 Kw

#### DIMENSION:

Mass	1200 kg
Settled for transport	1600x1200x1490(h) mm

### RECOMMENDATIONS

Follow the indications stated on European Directive and National Laws about the safety on the place to which the machine should be delivered.

- Individual protection;
- Safety and health on working place;
- Signage and safety advises;
- Environmental protection and safeguard (correct waste and run down oils disposal, etc.).

#### Officine Maccaferri S.p.A.

Via Kennedy, 10 - 40069 Zola Predosa (BO) - Italy  
 Tel. (+39) 051-6436000 - Fax (+39) 051-6436201  
 E-mail: comes@maccaferri.com - Web site: www.officinemaccaferri.com

Bureau Veritas Certified Quality System Company  
 with SINCERT's and UKAS' s accreditation.